

Fiche technique T8

Model		T8-10W-G-60-2	T8-22W-G-120-2	T8-30W-G-120
Photometric data 	Luminous flux (lumen)	1000lm	2200lm	3000lm
	Luminous intensity (candela)	120	300	300
	Color temperature	7000K	7000K	700K
	Color Rendering Index (CRI)	80	80	80
	Beam angle	320	320	320
	Start-up time	0.2S	0.2S	0.2S
	Warm-up time	0.2S	0.2S	0.2S
	Lumen maintenance factor after 6000 hrs	0.85	0.85	0.85
	Incandescent equivalent			
	Lamp survival factor after 6000h	98%	98%	98%
Electrical data	Voltage	220-240V	220-240V	220-240V
	Wattage	10W	22W	30W
	Rated current (input) in mA	55mA	135mA	146mA
	Lamp power factor	>0.5	>0.5	>0.5
	kWh/1000h	10	22	30

Additional product data	Cap type	G13	G13	G13
	LED type	SMD2835	SMD2835	SMD2835
	LED chip	san'an	san'an	san'an
	Number of LEDs	44	88	96
	Housing material	Glass	Glass	Glass
	Average life span	30000h	30000h	30000h
	Switching cycles	15000	15000	15000
	Dimmable yes/no	NO	NO	NO
	If dimming yes, trailing edge or leading edge	NO	NO	NO
	International Protection Rating	IP20	IP20	IP20
	Item dimensions	Ø2.6*60CM	Ø2.6*120CM	Ø2.6*120CM
	Mercury content	NO	NO	NO
Shipping	Dimensions of colour box	63*15.5*15.5CM	124*15.5*15.5CM	124*15.5*15.5CM
	master carton weight in g (empty)	0.7KG	2.2KG	2.2KG
	Item weight in g	100g	200g	200g
	PCS /CTN	25PCS/CTN	25PCS/CTN	25PCS/CTN
	Dimensions of master carton	63*16*19CM	123*16*19CM	123*16*19CM
	Net weight of master carton	2.5kg	5kg	5kg
	Gross weight of master carton	3.8kg	7.2kg	7.2kg